SAFETY DATA SHEET Jan, 2024

SECTION 1: PRODUCT AND COMPANY INDENTIFICATION

Product Name: Abrasive Cutting Wheels Manufacturer Name: Metlab Corporation Address: 4011 Hyde Park Blvd.

Niagara Falls NY 14305

Website: www.metlabcorp.com

Telephone Number: 800-828-6866 Emergency Number: 888-255-3924 Fax: 800-828-6866

SECTION 2: HAZARD(S) IDENTIFICATION

As sold, this product is a manufactured article. During processing, dust generated has the following hazards:

Classification:

Physical	Health	Environment
Not Hazardous	Eye Irritant Category 2	Not Hazardous
	Specific Target Organ Toxicity –	
	Single Exposure Category 3	

Hazards not otherwise classified: None

Symbol(s):



Signal Word: Warning!

Hazard statement(s):

H320 Causes eye irritation

H335 May cause respiratory irritation

Precautionary statement(s):

P260 Do not breathe dust

P264 Wash thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P280 Wear eye protection

P314 Get medical attention if you feel unwell

P501 Dispose of contents in accordance with local, state and

federal regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Products may contain any of the following ingredients:

CHEMICAL IDENTITY	CAS NUMBER	PERCENT UP TO:
Aluminum Oxide	1344-28-1	95%
Silicon Carbide	409-21-2	95%
Phenolic Resin	9003-35-4	20%
Sulfur	7704-34-9	15%
Potassium Fluoroborate	14075-53-7	10%
Cryolite	13775-53-6	20%
Dixie Clay	1332-58-7	35%
Calcium Sulfate	7778-18-9	15%
Red Iron Oxide	1332-37-2	20%
Natural Rubber		35%
Synthetic Rubber		35%
Hydrated Lime	1305-62-0	10%
Ultramarine Blue	57455-37-5	10%
Zinc Oxide	1314-13-2	10%

SECTION 4: FIRST-AID MEASURES

Inhalation: If dust from cutting is inhaled, remove the affected person to fresh air. If symptoms

persist, get medical attention.

Ingestion: Accidental ingestion of this material is unlikely. If this does occur, watch person for

several days to make sure intestinal blockage does not occur. If symptoms persist, call a

physician.

Skin Contact: Immediately wash skin with soap and water. If irritation develops or persists seek

medical attention.

Eye Contact: Flush eyes with large quantities of water. If irritation persists, obtain medical assistance.

SECTION 5: FIRE-FIGHTING MEASURES

Flammable Properties: Non Flammable

Flash Point: None

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires

Protective Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand and full

protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods for containment: Containment of this material should not be necessary.

Methods for cleanup: Sweep up for disposal. Avoid creating dusty conditions. Dispose of in accordance

with Local, State and Federal regulations.

SECTION 7: HANDLING AND STORAGE

Handling: Always handle and store wheels in a careful manner.

Always visually inspect all wheels before mounting.

Always check machine speed against the established maximum safe operating speed

marked on the wheel.

Always check mounting flanges for equal and correct diameter.

Always use a safety guard covering at least one-half of the cutting wheel.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Local exhaust ventilation as necessary to keep dust levels below TLVs.

Eye Protection: Goggles or safety glasses with side shields are recommended.

Skin Protection: Protective gloves

Respiratory Protection: Approved dust respirators recommended if TLV is exceeded.

Hearing Protection: As needed

General Hygiene: Maintain good industrial hygiene and safety practices.

Ingredient	Guideline OSHA	Guideline ACGIH TLV
Aluminum Oxide	5mg/m3 (R)	10mg/m3
	15mg/m3 (T)	
Silicon Carbide	5mg/m3 (R)	10mg/m3
	15mg/m3 (T)	
Potassium Fluoroborate	2.5mg/m3	2.5mg/m3
Cryolite	2.5mg/m3	2.5mg/m3
Dixie Clay	5mg/m3	0.025mg/m3
Calcium Sulfate	5mg/m3 (R)	10mg/m3
	15mg/m3 (T)	
Red Iron Oxide	10mg/m3	5mg/m3
Hydrated Lime	5mg/m3	5mg/m3
Ultramarine Blue	5mg/m3	10mg/m3
Zinc Oxide	5mg/m3	5mg/m3

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:

Vapor Pressure:

None

Vapor Density:

None

Specific Gravity:

Melting Point:

None

Evaporation Rate: None Solubility in Water: None

Appearance and Odor: Gray, Brown, Reddish Brown, Black

May give off rubber odor in use.

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Overspeed and unsafe use practices

Hazardous Polymerization: Does not occur

Hazardous Decomposition: Dusts are generated by use. Use of coolants may produce other decomposition

products.

SECTION 11: TOXICOLOGICAL INFORMATION

No evidence of toxicity.

None of the ingredients are known carcinogens.

SECTION 12: ECOLOGICAL INFORMATION

Biodegradation: These products show similar degradation rates as vulcanized rubber and phenolic resins.

SECTION 13: DISPOSAL CONSIDERATIONS

Use standard waste disposal methods in accordance with applicable Local, State and Federal regulations.

SECTION 14: TRANSPORT INFORMATION

Not regulated as hazardous material for transportation.

SECTION 15: REGULATORY INFORMATION

None recorded

SECTION 16: OTHER INFORMATION

NFPA Rating: Health = 0 Flammability = 0 Instability -0

HMIS Rating: Health = 1 Flammability = 0 Physical Hazard = 0

SDS Revision Date: Jan 1, 2024